



### Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru


“Step Out From the Old to the New”

IS 7931-3 (1975): Automatic and semi-automatic welding equipment with self-adjusting arcs (MIG/MAG Processes): Part 3 Welding gun and ancillary equipment [ETD 21: Electric Welding Equipment]

“ज्ञान से एक नये भारत का निर्माण”

Satyanareshwar Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartṛhari—Nītiśākām

“Knowledge is such a treasure which cannot be stolen”





BLANK PAGE



PROTECTED BY COPYRIGHT

**IS : 7931 ( Part III ) - 1975**

*Indian Standard*

**SPECIFICATION FOR AUTOMATIC AND  
SEMI-AUTOMATIC WELDING EQUIPMENT  
WITH SELF-ADJUSTING ARCS  
( MIG/MAG PROCESSES )**

**PART III WELDING GUN AND ANCILLARY EQUIPMENT**

**(First Reprint JANUARY 1993 )**

**UDC 621.791.03:621.791.75**

**© Copyright 1976**

**BUREAU OF INDIAN STANDARDS  
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG  
NEW DELHI 110002**

**Gr 2**

**October 1976**

## *Indian Standard*

# SPECIFICATION FOR AUTOMATIC AND SEMI-AUTOMATIC WELDING EQUIPMENT WITH SELF-ADJUSTING ARCS ( MIG/MAG PROCESSES )

## PART III WELDING GUN AND ANCILLARY EQUIPMENT

Electric Welding Equipment Sectional Committee, ETDC 21

*Chairman*

SHRI J. A. MULYIL

*Representing*

Indian Oxygen Ltd, Calcutta

*Members*

SHRI A. C. LAHIRI ( *Alternate* to  
Shri J. A. Mulyil )

ASSISTANT DIRECTOR, WEAPON Naval Headquarters  
EQUIPMENT ( UNDER-WATER  
EQUIPMENT )

STAFF OFFICER ( WEAPON  
EQUIPMENT ) ( *Alternate* )

SHRI S. BHATIA Philips India Ltd, Bombay

SHRI H. D. CHICKERMANE ( *Alternate* )

SHRI P. COOMAR Sur Iron & Steel Co Pvt Ltd, Calcutta

SHRI P. K. NEOGI ( *Alternate* )

SHRI K. L. GARG Directorate General of Supplies & Disposals ( Inspection Wing ), New Delhi

SHRI V. S. KRIPALANI ( *Alternate* )

SHRI SUDHIR KUMAR HARI Malik Electricals ( Private ) Ltd, Bombay

SHRI S. K. CHAUDHARY ( *Alternate* )

SHRI N. K. MATHUR Bharat Heavy Electricals Ltd, Bhopal

Lt-Col N. I. K. MURTHY Department of Defence Production, Directorate of

SHRI V. S. SUGAR ( *Alternate* ) Standardization, Ministry of Defence

SHRI G. T. NIHALANI Advani-Oerlikon Private Ltd, Bombay

SHRI J. K. CHANDNA ( *Alternate* )

SHRI KESHAR SINGH Triveni Structural Ltd, Allahabad

SHRI T. A. RAMACHANDRAN Railway Board, Ministry of Railways

SHRI D. KALYANASUNDARAM ( *Alternate* )

( *Continued on page 2* )

© Copyright 1976

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act ( XIV of 1957 )* and  
reproduction in whole or in part by any means except with written permission of  
the publisher shall be deemed to be an infringement of copyright under the said Act.

**IS : 7931 ( Part III ) - 1975**

( Continued from page 1 )

<i>Members</i>	<i>Representing</i>
SHRI H. L. ROBERTS	Mazagon Dock Ltd, Bombay
SHRI M. K. SRIDHAR	Bharat Heavy Electricals Ltd, Tiruchirapalli
SHRI M. A. KESAVAN ( <i>Alternate</i> )	
SHRI N. S. SUBBANNA	Kirloskar Electric Co Ltd, Bangalore
SHRI M. GURUBASWARAJ ( <i>Alternate</i> )	
SHRI N. SHUNIVASAN, Director ( Elec tech )	Director General, ISI ( <i>Ex-officio Member</i> )
	<i>Secretary</i>
	SHRI N. DASSHARMA
	Deputy Director ( Elec tech ), ISI

## *Indian Standard*

# SPECIFICATION FOR AUTOMATIC AND SEMI-AUTOMATIC WELDING EQUIPMENT WITH SELF-ADJUSTING ARCS ( MIG/MAG PROCESSES )

## PART III WELDING GUN AND ANCILLARY EQUIPMENT

### 0. FOREWORD

**0.1** This Indian Standard ( Part III ) was adopted by the Indian Standards Institution on 30 December 1975, after the draft finalized by the Electric Welding Equipment Sectional Committee had been approved by the Electrotechnical Division Council

**0.2** There are numerous variations of arc welding processes using consumable electrode wires. The wire may be solid or composite, and with or without flux. In all these cases, the melting generally takes place in the presence of a shielding gas. This gas may be inert ( for example, argon ) or have a definite chemical activity at the high temperature of the electric arc ( for example, carbon dioxide ) when the shielding gas is inert the welding process is known as MIG process and when this gas has a definite chemical activity at the high temperature of the electric arc this process is called MAG process.

**0.3** Because of the wide variations in equipment and processes it is not practicable at present to specify the performance and the test requirements. These shall be a matter of agreement between the supplier and the purchaser.

**0.4** This standard on automatic and semi-automatic welding equipment is being issued in three parts. This part covers welding gun and ancillary equipment while dc generator power sources are covered in Part I and transformer rectifier power sources in Part II.

**0.5** In preparing this standard, assistance has been derived from the following:

ISO Doc. TA-76/72/E Specification of arc-welding equipment using consumable wires ( MIG-MAG processes ). International Organization for Standardization.

Document No. 71/42369 — Draft British Standard specification for arc welding plant, equipment and accessories ( *revision of BS 638-1966* ). British Standards Institution.

NEMA EW -1-1971 Electric arc-welding apparatus. National Electric Manufacturers' Association, USA.

## IS : 7931 ( Part III ) - 1975

**0.6** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS : 2-1960\*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard

---

### 1. SCOPE

**1.1** This standard ( Part III ) covers the general and safety requirements and test methods of welding gun and ancillary equipment for automatic and semi-automatic electric welding with self-adjusting arcs ( MIG/MAG processes )

### 2. TERMINOLOGY

**2.0** In addition to those given under **2.1** to **2.3**, the definitions given under 2 of IS 7931 ( Part I ) 1975† shall apply.

**2.1 Welding Gun** — A current carrying device which is held and guided by an operator and through which a continuous consumable electrode is fed to the welding arc around which a suitable shielding gas may flow from a nozzle at the exit end of the device.

**2.2 Welding Head** — A device for fulfilling the same functions as that of welding gun, which is mechanically supported when in use and may incorporate gas shielding means and may incorporate a wire feed mechanism

**2.3 Wire Feed Unit** — Equipment for feeding a continuous consumable electrode at a controlled rate to a welding gun or welding head.

### 3. DESIGN AND CONSTRUCTION

#### 3.1 Welding Guns

**3.1.0** The design and construction of welding guns shall satisfy the requirements specified in **3.1.1** to **3.1.17**.

**3.1.1** Guns shall be air, liquid or gas cooled.

**3.1.2** The guns shall be so designed that welding can be carried out with a minimum of effort by the operator and shall permit satisfactory feed of the specified range of wires when used with the approved wire feed unit.

---

\*Rules for rounding off numerical values ( revised ).

†Specification for automatic and semi-automatic welding equipment with self-adjusting arcs ( MIG/MAG processes ) - Part I dc welding generator power source

**3.1.3** The handle shall be so positioned as to prevent undue heating of the operator's hand. Hand guards, if fitted, shall not cause interference with the welding operation.

**3.1.4** Handles shall be constructed of or encased in insulating materials or they shall be insulated from the live parts

**3.1.5** The construction of handles shall be such that no dirt which is likely to cause danger of electric shock can lodge in joints, holes or other crevices, and that the live ends of pins or screws cannot become exposed in use

**3.1.6** All exposed metal with the exception of the contact tip shall be insulated from current carrying parts.

**3.1.7** The terminals for electrical connections shall be of adequate size so as to allow connections of cables of appropriate rating without being overheated under normal conditions of use

**3.1.8** The risk of damage due to continuous flexing of cables and hoses at the point of entry to the gun shall be kept to a minimum.

**3.1.9** Parts shall be adequately rated to prevent excessive temperature-rise.

**NOTE** — Because of the wide variation in equipment and processes it is not at present practicable to specify temperature-rise tests

**3.1.10** The gun shall be able to direct an adequate flow of shielding gas under all conditions of welding for which the gun is designed.

**3.1.11** The shielding gas and/or coolant flow to the gun shall be controlled by suitable means.

**3.1.12** Forced-cooled parts shall be protected by coolant flow failure devices which will prevent overheating in the event of failure.

**3.1.13** Gas nozzles shall be readily replaceable and shall be made so as to remain as free from spatter as possible.

**3.1.14** All parts affected by change of wire size shall have the correct dimensions for trouble-free wire feed and shall be permanently identifiable for size and type of wire.

**3.1.15** For arc spot welding application, the nozzles shall be so designed that they rest on the work-piece and gas is allowed to flow around the weld

**3.1.16** The voltage to earth of gun mounted controls shall not exceed 100 V dc or 60 V ac rms.

**IS : 7931 ( Part III ) - 1975**

**3.1.17** Controls and parts needing regular maintenance shall be replaceable.

**3.2 Cables and Hoses**

**3.2.0** The design and construction of cables and hoses shall satisfy the following requirements.

**3.2.1** Cables and hoses, between the power source or wire feed unit and the gun, which are attached to the gun shall be capable of carrying:

- a) welding current,
- b) shielding gas,
- c) cooling liquid or gas ( if required ),
- d) electrode wire, and
- e) control leads and auxiliary supplies.

**3.2.2** Cables and hoses shall be capable of being flexed without undue wear or blockage of wire feed and gas/liquid flow.

**3.2.3** Cables and hoses shall be terminated at the end remote from the gun for convenient connection to the various services.

**3.2.4** Cables, hoses and/or complete assemblies shall be readily replaceable.

**3.3 Ancillary Equipment**

**3.3.1** The wire feed motor shall have provision for varying the electrode wire feed speed and shall be continuously rated and suitably protected. It shall be capable of being started frequently without injury or overheating and, together with the drive unit, shall be suitably insulated.

**3.3.2** The drive unit shall have provision for easy replacement of electrode wire and for change of electrode wire size. Drive roll pressure shall be adjustable and a quick release device shall be fitted.

**3.3.3** The wire reel shall be insulated from earth and easily detachable. Where necessary, the wire reel shall be suitably guarded to prevent accidental contact. Means shall be provided for preventing over-run of wire.

**4. MARKING**

**4.1** Following information shall be legibly and indelibly marked on the welding gun and ancillary equipment:

- a) Manufacturer's name or trade-mark, and
- b) Manufacturer's type and serial number.

**AMENDMENT NO. 1      MAY 1978**

**TO**

**IS : 7931 (Part III) - 1975 SPECIFICATION FOR  
AUTOMATIC AND SEMI-AUTOMATIC WELDING  
EQUIPMENT WITH SELF-ADJUSTING ARCS  
+       (MIG/MAG PROCESSES)**

**PART III   WELDING GUN AND ANCILLARY EQUIPMENT**

**Addendum**

*(Page 7, clause 5.1)* — Add the following para at the end of this clause:

‘For this test, the surface of the handle shall be wrapped securely in metal foil to within 12 mm of the ends of the handle. The handle shall be wiped dry before wrapping with foil’

**(ETDC 21)**

---

Reprography Unit, BIS, New Delhi, India

**4.1.1** Welding gun and ancillary equipment may also be marked with the ISI Certification Mark.

**NOTE** -- The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution ( Certification Marks ) Act and the Rules and Regulations made thereunder. The ISI mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

## 5. TYPE TESTS

**5.0** Gun shall be subjected to the following type tests in the order prescribed:

- a) Insulation resistance test ( *see 5.1* ),
- b) High voltage test ( *see 5.2* ), and
- c) Performance test ( *see 5.3* ).

These tests shall also be carried out as routine tests

**5.1 Insulation Resistance Test** — The insulation resistance shall be measured with a dc voltage of about 500 volts applied for a sufficient time for the reading of the indicator to become practically steady, such voltage being taken from an independent source or generated in the measuring instrument. The insulation resistance shall be not less than 2 megohm.

**5.2 High Voltage Test** — Following the test for insulation resistance, the gun shall be dried for 1 hour at a temperature not exceeding 40°C, and then with the metal foil(s) still in position it shall be capable of withstanding a voltage of 2 000 volts rms at 50 Hz applied for one minute between the contact tip and the foil on the handle.

**5.3 Performance Test** — The criteria for performance test and the requirements shall be a matter of agreement between the supplier and the purchaser.

## BUREAU OF INDIAN STANDARDS

### *Headquarters :*

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones	331 01 31	Telegrams	Manaksanstha
	331 13 75	(Common to all Offices)	

### *Regional Offices :*

Central	Manak Bhavan, 9, Bahadur Shah Zafar Marg NEW DELHI 110002	Telephone
• Eastern	1/14 C.I.T. Scheme VII M. V.I.P. Road, Maniktola, CALCUTTA 700054	331 01 31
	SCO 445-446, Sector 35-C, CHANDIGARH 160036	331 13 75
	C.I.T Campus, IV Cross Road, MADRAS 600113	2 18 43
† Western	Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	41 29 16
		6 32 92 95

### *Branch Offices :*

'Pushpak', Nurmoohamed Shaikh Marg, Khanpur, AHMADABAD 380001	2 63 48
Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road. BANGALORE 560058	39 49 55
Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar. BHOPAL 462003	55 40 21
Plot No. 82/83, Lewis Road, BHUBANESHWAR 751002	5 36 27
Kalai Kathi Building, 6/48-A Avanasi Road, COIMBATORE 641037	2 67 05
Q Marking Centre, N.H. IV, N.I.T., FARIDABAD 121001	—
Savitri Complex, 116 G, T Road, GHAZIABAD 201001	8-71 19 96
53/5 Ward No. 29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003	3 31 77
5-8-56C L. N. Gupta Marg, ( Nampally Station Road ) HYDERABAD 500001	23 10 83
R14 Yudhister Marg, C Scheme, JAIPUR 302005	6 34 71
117/418 B Sarvodaya Nagar, KANPUR 208005	21 68 76
Plot No. A-9, House No 561/63, Sindhu Nagar, Kanpur Road, LUCKNOW 226005	5 55 07
Patliputra Industrial Estate, PATNA 800013	6 23 05
District Industries Centre Complex, Bagh-e-Ali Maidan, SRINAGAR 190011	—
T C. No. 14/1421, University P. O., Palayam. THIRUVANANTHAPURAM 695034	6 21 04
<b>Inspection Offices (With Sale Point)</b>	
Pushpanjali, First Floor, 205-A West High Court Road Shankar Nagar Square, NAGPUR 440010	52 61 71
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005	5 24 35
<hr/>	
*Sales Office Calcutta is at 5 Chowringhee Approach, P. O. Princep Street, CALCUTTA	27 68 00
† Sales Office is at Novelty Chambers, Grant Road, BOMBAY	89 65 28
‡ Sales Office is at Unity Building, Narasimharaja Square, BANGALORE	22 39 71

**Reprography Unit, BIS, New Delhi, India**